

# Oprawa LED Downlight



Model	P	lm	K	°	V	CRI	PF	°C	lm/W	mm	kg
Downlight 8W IP65	8 W	560 lm	4000 K	90°	195-255 V	> 80	> 0.90	-20 ÷ 40°C	70 lm/W	Ø105x H50 mm	0.2 kg
Downlight 18W IP44	18 W	1530 lm	4000 K	90°	195-255 V	> 80	> 0.90	-20 ÷ 40°C	85 lm/W	Ø152x H50 mm	0.4 kg
Downlight 24W IP44	24 W	2040 lm	4000 K	90°	195-255 V	> 80	> 0.90	-20 ÷ 40°C	85 lm/W	Ø152x H50 mm	0.4 kg
Downlight 30W IP44	30 W	2550 lm	4000 K	90°	195-255 V	> 80	> 0.90	-20 ÷ 40°C	85 lm/W	Ø203x H50 mm	0.6 kg

LEDOLUX

## MATERIAŁ

Obudowa: aluminium  
Dyfuzor: poliwęglan (PC)

## MONTAŻ

Montaż: podtynkowy

## ZASILANIE

Zasilacz: Ledolux wewnątrz obudowy

## ZASTOSOWANIE

Obiekty: sanitarne, biurowe, handlowe, instytucjonalne

## FOTOMETRIA

