



TECHNICAL INFORMATION

Watts:	50
Lumens:	4000
Input Power:	AC:220-240V, 50Hz
Long Life:	30,000 Hours
Unit Color:	Black
Body Type:	Die Cast Aluminium
PF:	>0.9
LED Chip Type:	SMD-Samsung Chip
CRI:	>80
Operation Temperature:	-20°C to +45°C
Dimmable:	No
Beam Angle:	100°
Color Temperature:	6400K
Dimension:	223x57.06x234.3mm
Sensor Type:	PIR
Detection Distance:	2-8m(


PIR SENSOR PRO

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 471 - 933 938

[View more details](#)



IP65
RATING



5 YEAR
WARRANTY



IK 05



CRI > 80



SAVE UP TO
85%
ENERGY

FEATURES

- PIR Sensor Floodlight built with adjustable sensor head
- Designed with Manual Override functionality
- IP65 protection - Built with 1 Meter wire.
- Designed with high efficiency LED Samsung Chips
- Built in driver - no external power supply required
- Built Strong and durable with Die Cast Aluminium - Corrosion resistant design
- Suitable for driveways, gardens, patio, building, security lighting etc.

CE/EMC

CE/LVD



PACKAGING

Gross Weight (Kgs): 1.07
Unit CBM: 0.005
Dimension: 223x57.06x234.3mm

MASTER BOX PACKAGING

Box Qty: 8
Qty Per Pallet: 240
Length (Box) mm: 80
Width (Box) mm: 250
Height (Box) mm: 250

LISTING DETAILS

Commodity Code: 9405403990
Ean Code: 3800157631273